

Flow over a building with elastic membrane roof

Iñaki Çaldichoury

Facundo Del Pin

Rodrigo Paz

LSDYNA ICFD solver
Dev version SVN 109309








LSTC
Livermore Software
Technology Corp.

A viscous flow passes over a building preloaded by gravity. Non linear vibrations due to fluid structure interaction occur. The mesh size of the roof is made of 200 nodes and the chosen timestep is $0.005s$.



Quantity	Units	Value
ρ_f	$kg.m^{-3}$	1.25
μ_f	$Pa.s$	0.1
roofthickness	m	0.01
E	Pa	10^9
ρ_s	$kg.m^{-3}$	1000
ν	–	0.



All units are in meters and m/s






Results- Fluid Vertical Velocity behind the roof







- [1] B. Hübner, E. Walhorn, and D. Dinkler, “A monolithic approach to fluid–structure interaction using space–time finite elements,” *Computer Methods in Applied Mechanics and Engineering*, vol. 193, no. 23–26, pp. 2087 – 2104, 2004.

The test case(s) described herein are for illustrative purposes only. LSTC does not warrant that a user of these or other LS-DYNA features will experience the same or similar results or that a feature will meet the user's particular requirements or operate error free. FURTHERMORE, THERE ARE NO WARRANTIES, EITHER EXPRESS OR IMPLIED, ORAL OR WRITTEN, WITH RESPECT TO THE DOCUMENTATION AND SOFTWARE DESCRIBED HEREIN INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTIES (i) OF MERCHANTABILITY, OR (ii) FITNESS FOR A PARTICULAR PURPOSES, OR (iii) ARISING FROM COURSE OF PERFORMANCE OR DEALING, OR FROM USAGE OF TRADE OR. THE REMEDIES SET FORTH HEREIN ARE EXCLUSIVE AND IN LIEU OF ALL OTHER REMEDIES FOR BREACH OF WARRANTY.