

Tuned Liquid Damping Problem

SPHERIC Test9

Iñaki Çaldichoury

Facundo Del Pin

Rodrigo Paz


LSDYNA ICFD solver

Dev version SVN 108068



LSTC
Livermore Software
Technology Corp.

The tank, initially in equilibrium, is free to rotate and its movement is induced by a weight that has a prescribed periodic movement along an initially horizontal rail attached to the rotation center of the tank which periodically displaces the center of gravity. The breaking waves and sloshing dynamics of the fluids placed inside the tank affect the damping characteristics of the system.



Case Description

The analytical model used to describe the behavior of the system is described in the following equations:

$$[I_0 + m\xi_m^2(t)]\ddot{\phi} + 2m\xi_m(t)\dot{\xi}_m(t)\dot{\phi} - gS_G \sin(\phi) + mg\xi_m(t)\cos(\phi) = Q_{damp}(t) + Q_{fluid}(t) \quad (1)$$



$$Q_{damp}(t) = -K_{df} \text{sign}(\dot{\phi}) - B_\phi \dot{\phi} \quad (2)$$

ϕ the roll angle, g the gravity constant, I_0 and S_G the polar moment of inertia and static moment of the rigid system with respect to the rotation center, $\xi_m(t)$ and $\dot{\xi}_m(t)$ the moving mass position and velocity, K_{df} the dry friction coefficient, B_ϕ the linear damping coefficient and $Q_{fluid}(t)$ the damping moment introduced by the fluid to be captured by the simulation.


Quantity	Units	Value
S_G	$kg.m$	-29.2
I_0	$kg.m^2$	26.9
K_{df}	$N.M$	0.540
B_ϕ	$N.m.rad^{-1}.s$	0.326
w_0	$rad.s^{-1}$	3.26

Three fluids are tested, water with $\rho = 998 \text{ kg.m}^{-3}$ and $\mu = 8.94e^{-4} \text{ kg.m}^{-1}.s^{-1}$, oil with $\rho = 990 \text{ kg.m}^{-3}$ and $\mu = 0.045 \text{ kg.m}^{-1}.s^{-1}$ and glycerin with $\rho = 1261 \text{ kg.m}^{-3}$ and $\mu = 0934 \text{ kg.m}^{-1}.s^{-1}$


Time = 10.9 s





Time = 11.4 s





Time = 8.6 s





Time = 9.2 s









Time = 8.7 s



Time = 9.2 s







- [1] G. Bulian, A. Souto-Iglesias, L. Delorme, and E. Botia-Vera, "Smoothed particle hydrodynamics (sph) simulation of a tuned liquid damper," *Journal of Hydraulic Research*, vol. 48, no. sup1, pp. 28–39, 2010.
- [2] E. Bota-Vera, A. Souto-Iglesias, G. Bulian, and L. Lobovsky, "Three sph novel benchmark test cases for free surface flows," 5th ERCOFTAC SPHERIC workshop on SPH applications, 2010.

The test case(s) described herein are for illustrative purposes only. LSTC does not warrant that a user of these or other LS-DYNA features will experience the same or similar results or that a feature will meet the user's particular requirements or operate error free. FURTHERMORE, THERE ARE NO WARRANTIES, EITHER EXPRESS OR IMPLIED, ORAL OR WRITTEN, WITH RESPECT TO THE DOCUMENTATION AND SOFTWARE DESCRIBED HEREIN INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTIES (i) OF MERCHANTABILITY, OR (ii) FITNESS FOR A PARTICULAR PURPOSES, OR (iii) ARISING FROM COURSE OF PERFORMANCE OR DEALING, OR FROM USAGE OF TRADE OR. THE REMEDIES SET FORTH HEREIN ARE EXCLUSIVE AND IN LIEU OF ALL OTHER REMEDIES FOR BREACH OF WARRANTY.